

Battery specifications - Varta motorcycle batteries

Part No.	JIS Ref.	UK Ref.	Liquifix	Breather vent position	Cap in Ah. @ 20Hr. rate	Cold start EN	Bench charge AMPS	Dimensions			Weight (filled) Kg	Layout	Terminals	Notes
								L (mm)	W (mm)	H (mm)				
6 Volt														
002014001	6N2A-2C-3	819		RIGHT	2	10	1.0	71	47	106	0.6	0	2	9,20,26
004012001	6N4B-2A, 6N4B-2A-3	842		LEFT	4	10	1.0	102	48	96	1.0	1	2	9,19,20,26
004013001	6N4A-4D	839		BEHIND	4	10	1.0	57	61	131	0.8	3	2	9,20,26
004014001	6N4-2A-1, 6N4-2A-4, 6N4A-2A-7	837		LEFT	4	10	1.0	71	71	96	0.9	1	2	9,19,20,26
004015001	6N4C-1B	-		RIGHT	4	10	1.0	71	71	105	1.2	0	2	9,20,2
006011003	6N6-3B	852		ON TOP	6	30	1.0	100	57	111	1.3	2	2	9,20,26
006012003	6N6-3B-1	-		RIGHT	6	30	1.0	99	57	111	1.3	2	2	9,20,26
006013003	6N6-1D-2	-		BEHIND	6	30	1.0	100	58	112	1.3	0	2	9,26
007014003	B39-6	802			7	30	1.0	129	52	128	1.6	0	2	9,26
008011004	B49-6	-			8	40	1.0	95	85	166	2.2	1	2	9,26
011400008	6N11A-1B	-		RIGHT	11	80	1.0	122	62	132	2.2	2	2	9,20,26
012014008	6N11A-3A	859		LEFT	12	80	1.0	123	61	137	2.3	3	2	9,20,26
012025008	6N12A-2D	-		BEHIND	12	80	1.0	156	57	116	2.4	1	2	9,26
016012008	B38-6A	-			16	80	1.0	122	82	165	2.5	2	2	9,20,26
12 Volt														
503011001	YB2.5L-C-2	-		FRONT	2.5	10	1.0	81	71	106	1.0	0	2	9,20,26
503012001	YB3L-A	-		LEFT	3	10	1.0	100	58	112	1.3	0	2	9,20,26
503013001	YB3L-B	-		RIGHT	3	10	1.0	100	58	112	1.3	0	2	9,20,26
503014003	YT4L-BS	-	•	SEALED	3	30	1.0	104	71	106	1.4	0	2	24
503902004	YT4B-4, YT4B-BS	-	•	SEALED	3	40	1.0	114	49	86	1.6	4	Push On	24
503903004	YTR4A-BS	-	•	SEALED	3	40	1.0	114	49	86	1.8	4	2	24
504011002	YB4L-B	-		RIGHT	4	20	1.0	121	71	93	1.5	0	2	9,20,26
504012003	YTX5L-BS	-	•	SEALED	4	30	1.0	114	71	106	1.9	0	2	24
505012003	YB5L-B, 12N5-3B	864		RIGHT	5	30	1.0	121	61	131	2.0	0	2	9,20,26
505901009	YTZ6S-BS	-	•	SEALED	5	90	1.0	113	70	105	4.2	0	2	24
506011004	12N5.5-3B	866		RIGHT	6	40	1.0	136	61	131	2.4	0	2	9,20,26
506012004	12N5.5A-3B	870		RIGHT	6	40	1.0	104	91	115	2.4	0	2	9,20,26
506014005	YTX7L-BS	-	•	SEALED	6	50	1.0	114	71	131	2.5	0	2	24
506015005	YTX7A-BS	-	•	SEALED	6	50	1.0	151	88	94	2.6	1	2	24
507012004	YB7L-B, 12N7-3B	-		RIGHT	7	40	1.0	136	76	135	3.0	0	2	9,20,26
507013004	12N7-4A	-		LEFT	7	40	1.0	136	76	135	3.0	1	2	9,20,26
507101008	YB7C-A	-		RIGHT	7	8	1.0	130	90	114	2.3	0	2	9,20,26
507901012		-		SEALED	7	120	1.0	150	66	94	2.7	1	2	24
507902011	YTZ7S, YTX7S-BS	-	•	SEALED	7	110	1.0	113	70	105	4.9	1	2	24
508012008	YTX9-BS	-	•	SEALED	8	80	1.0	152	88	106	3.0	1	2	24
508013008	YB7-A	-		LEFT	8	80	1.0	137	76	134	3.0	1	2	9,20,26
508901015	YTZ10S, YTZ10S-BS	-	•	SEALED	8	150	1.0	150	87	93	5.2	1	2	24
509014008	YB9-B, 12N9-4B-1	885		RIGHT	9	80	1.0	136	76	140	3.2	1	2	9,20,26
509015008	YB9L-B, 12N9-3B	868		RIGHT	9	80	1.0	136	76	140	3.2	0	2	9,20,26
509016008	YB9L-A2	-		LEFT	9	80	1.0	135	75	139	3.1	0	2	9,20,26
509901020	YTZ12S-4, YTZ12S-BS	-	•	SEALED	9	200	1.0	150	87	110	5.8	1	2	24
509902008	YT9B-4, YT9B-BS	-	•	SEALED	9	80	1.0	149	70	105	2.7	1	2	24
510012009	YTX12-BS	-	•	SEALED	10	90	1.0	152	88	131	4.2	1	2	24
510901012	YTR9-4, YTR9-BS	-	•	SEALED	10	120	1.0	150	87	105	3.8	1	2	24
511012009	YB10L-A2, 12N10-3A	890		LEFT	11	90	1.0	136	91	147	4.8	0	2	9,20,26
511013009	YB10L-B2, YB10L-B, 12N10-3B	-		RIGHT	11	90	1.0	136	91	146	4.6	0	2	9,20,26
511901014	YT12A-4, YT12A-BS	-	•	SEALED	11	140	1.0	150	88	105	4.1	1	2	24
511902023	YTZ14S-4, YTZ14S-BS	-	•	SEALED	11	230	1.0	150	87	110	6.4	1	2	24
512011012	YB12A-A, 12N12A-4A-1	897		LEFT	12	120	1.0	136	81	142	4.2	1	2	9,20,26
512012012	YB12B-B2	-		RIGHT	12	120	1.0	161	91	131	4.0	1	2	9,20,26
512013012	YB12AL-A, YB12AL-A2	-		LEFT	12	120	1.0	136	82	162	5.0	0	2	9,19,20,26
512014010	YTX14-BS	-	•	SEALED	12	100	1.0	152	88	147	4.6	1	2	24
512015012	YB12A-B	-		RIGHT	12	120	1.0	136	82	162	4.1	1	2	9,20,26
512901019		-		SEALED	12	190	1.0	151	70	131	4.1	1	2	24
512903013	YT14B-4, YT14B-BS	-	•	SEALED	12	130	1.0	152	70	150	5.5	1	2	24
514011014	YB14L-A2, 12N14-3A	898		LEFT	14	140	1.0	135	90	167	4.6	0	2	9,20,26
514012014	YB14-A2	-		LEFT	14	140	1.0	136	91	168	4.5	1	2	9,20,26
514013014	YB14L-B2	-		RIGHT	14	140	1.0	136	91	168	4.5	0	2	9,20,26
514014014	YB14-B2	-		RIGHT	14	140	1.0	136	91	168	4.5	1	2	9,20,26
514400019	YB14L-A1	-		LEFT	14	140	1.0	135	91	167	5.8	0	2	9,20,26
514901022	YTX16BS-1	-		SEALED	14	220	1.0	150	87	161	4.7	0	2	24
514902022	YTS16BS	-		SEALED	14	220	1.0	150	87	161	4.7	1	2	24
516015016	YB16B-A, YB16B-A1	-		LEFT	16	160	2.0	160	90	161	5.0	1	2	9,19,20,26
516016012	YB16AL-A2	-		LEFT	16	120	2.0	207	72	164	5.3	0	2	9,20,26
518014015	BMW ONLY	-		RIGHT	18	150	2.0	186	82	173	8.0	0	2	9,20,26
518015018	YB18L-A	-		LEFT	18	180	2.0	181	92	164	7.2	0	2	9,20,2
518400018	YB18-A	-		LEFT	18	180	2.0	181	92	164	7.2	1	2	9,20,26
518901026	YTX20L-BS	-		SEALED	18	260	2.0	177	88	156	7.8	0	2	24
518902026	YTX20-BS	-		SEALED	18	260	2.0	177	88	156	7.8	1	2	24
518903020	CP18-12	-	•		18	200	2.0	181	76	167	7.9	1	2	24
519011019	YB16L-B	103		RIGHT	19	190	2.0	176	101	156	6.3	0	2	9,20,26
519012019	YB16-B	-		RIGHT	19	190	2.0	176	101	156	6.3	1	2	9,20,26
519013017	BMW ONLY	-		LEFT	19	170	2.0	186	82	171	6.0	0	2	9,20,26
519014018	YB16CL-B	-		RIGHT	19	180	2.0	176	101	176	6.3	0	2	9,20,26
519901017		-	AGM		19	170	2.0	186	82	173	8.0	1	2	
520012020	Y50-N18L-A, Y50N-18L-A2	-		LEFT	20	200	2.0	206	92	163	7.0	0	2	9,20,26
520016020	SY50-N18L-AT	-		LEFT	20	200	2.0	206	91	170	6.5	0	2	9,20,26
520400026	12N20AH	-		RIGHT	20	260	2.0	186	81	170	7.4	0	2	9,20,26
520401026	Y50-N18L-A3	-		LEFT	20	260	2.0	206	91	164	7.4	0	2	9,20,26
524101020	12N24-4,	896		RIGHT	24	300	3.0	186	130	171	10.0	1	2	
525015022	Y60-N24L-A	-		RIGHT	25	220	2.0	186	130	171	10.0	0	2	9,20,26
528400030	Y60-N24AL-B	-		RIGHT	28	300	3.0	185	125	176	10.0	0	2	9,20,26
530030030	YB60-N24L-A, B68-12, BMW	895		RIGHT	30	300	3.0	186	130	171	10.0	0	2	9,20,26
532011024		-			32	240	3.0	233	132	168	8.2	1	2	9,20,26
532036024	YHD-12	-		LEFT	32	240	3.0	243	132	165	8.3	1	2	9,20,26